

Specifications

Features

Image Sensor	: 1/2.8"CMOS, 2.14MP
Signal Format(SDI)	: 1080P60, 1080P50, 1080P30, 1080P25, 1080I60, 1080I50, 720P60, 720P50
Focal	: f=3.9mm-46.8mm
Iris	: F1.6-F2.8
Optical Zoom	: 12x
Digital Zoom	: 12x
Field of View	: 72.5°-6.3°
Focus	: Auto, Manual, PTZ Push, One Push
Min. Illumination	: 0.5Lux (Colour), 0.1Lux (B/W)
Shutter Speed	: 1/25-1/10,000s
AGC	: Auto/Manual
White Balance	: Auto, Indoor, Outdoor, One Push Manual, Auto Track
AE Control	: Auto, Manual, Shutter Priority, Iris Priority
S/N	: ≥50dB
DNR	: 2D/3D
BLC	: Support

Camera

Pan Range	: 90°~+90°
Tilt Range	: -30°~+90°
Pan Speed	: 0.1°~120°/s
Tilt Speed	: 0.1°~80°/s
Preset Number	: 256
OSD	: Yes
Image Flip	: Yes

Network

Max. Image Size	: 1920×1080 @60 fps
Video Compression	: H.265,H.264
Audio Compression	: AAC
Protocol	: HTTP,RTSP,RTMP,RTP,TCP,UDP,ONVIF
Dual Stream	: Support




PeopleLink

Interface

Video Output	: 1×HDMI Interface,1×3G-SDI Interface,
Audio Input	: 2×LINE IN, including one channel with EC
Audio Output	: 1×LINE OUT
Network Interface	: 1×10M/100M
USB Interface	: 1×USB2.0
Control Interface	: 1×RS-232

General

Control Protocol	: VISCA, PELCO-P, PELCO-D
Address	: 0~63
Power Supply	: DC12V
Power Consumption	: <50W
Working Temp	: 0°C ~ +40°C
Storage Temp	: -20°C ~ +60°C
Dimension (L×W×H)	: 500 mm x 162mm x 137mm
Weight	: 3kg



LuminoMatrix Digital Technologies